












**BSP  
G**Thread Gaz Whitworth  
Filetage Whitworth Gaz  
Rosca Whitworth GasDIN ISO 228 Norm  
Norme DIN ISO 228  
Norma DIN ISO 228**MACHINE CUTTING TAP**  
**TARAUD MACHINE Á COUPE**  
**MACHO DE CORTE A MÁQUINA****DIN  
ISO 228****DIN  
5156****HSS  
E****BRIGHT  
UNCOATED****2,5xd****A****B****F1****H1****N2****N3**

9633051	Ø	P	L	l1	d	DIN	□	●Ø
963305100180280	G 1/8"	28	90	18	7	5156	5,5	8,8
963305100140190	G 1/4"	19	100	22	11	5156	9	11,8
963305100380190	G 3/8"	19	100	25	12	5156	9	15,3
963305100120140	G 1/2"	14	125	25	16	5156	12	19
963305100580140	G 5/8"	14	125	25	16,0	5156	14,5	21,0
963305100340140	G 3/4"	14	125	25	18	5156	16	24,5
963305100780140	G 7/8"	14	140	28	20,0	5156	18,0	28,3
963305110000110	G 1"	14	140	28	20	5156	20	30,8
963305111800110	G1 1/8	11	160	36	25,0	5156	22,0	35,5
963305110140110	G1 1/4	11	160	36	25	5156	24	39,5
963305111380110	G1 3/8	11	170	40	32,0	5156	29,0	42,0
963305110120110	G1 1/2	11	190	32	36	5156	29	45,5
963305111340110	G1 3/4	11	190	40	40,0	5156	32,0	51,4
963305120000110	G 2"	11	190	40	40,0	5156	35,0	57,2

**BSPT  
Rc**Taper taps  
Tarauds coniques  
Machos cónicosBS 21 Norm  
Norme BS 21  
Norma BS 21**MACHINE CUTTING TAP**  
**TARAUD MACHINE Á COUPE**  
**MACHO DE CORTE A MÁQUINA****simDIN  
5156****HSS****BRIGHT  
UNCOATED****2,5xd****A****B****C****K****L**

9663011	Ø	P	L	l1	d	DIN	□
966301100180280	RC 1/8	27	90	15	8	5156	6,2
966301100140190	RC 1/4	19	100	21	11	5156	9
966301100380190	RC 3/8	19	110	21	14	5156	11
966301100120140	RC 1/2	14	140	27	18	5156	14,5
966301100340140	RC 3/4	11,5	160	27	25	5156	18

