














**NPT**Taper pipe thread  
Filet conique gaz  
Rosca cónica para tuboASA B 1.1 Norm  
Norme ASA B 1.1  
Norma ASA B 1.1**MACHINE CUTTING TAP**  
**TARAUD MACHINE Á COUPE**  
**MACHO DE CORTE A MÁQUINA****TIVOLY  
NORM****HSS****BRIGHT  
UNCOATED****2,5xd****A****B****C****K****L**

9643101	Ø	P	L	l1	d	□
964310100180270	NPT1/8	27	70	15	8	6,2
964310100140180	NPT1/4	18	70	21	11	9
964310100380180	NPT3/8	18	75	21	14	11
964310100120140	NPT1/2	14	80	27	18	14,5
964310100340140	NPT3/4	14	90	27	22	18
964310110000115	NPT1"	11,5	110	33	25	20

**PG**Thread DIN 40430  
Filet DIN 40430  
Rosca DIN 40430**FOR ELECTRICAL CONDUCTIONS**  
**FOR CONDUCTIONS ELECTRIQUES**  
**PARA CONDUCTOS ELECTRICOS****DIN  
40433****HSS  
E****BRIGHT  
UNCOATED****2,5xd****A****B****C****K****L**

9653011	Ø	P	L	l1	d	DIN	□	•Ø
965301100700200	PG 7	20	100	22	9	40433	7	11,40
965301100900180	PG 9	18	100	25	12	40433	9	14
965301101100180	PG 11	18	110	25	14	40433	11	17,25
965301101350180	PG13,5	18	125	25	16	40433	12	19
965301101600180	PG 16	18	125	25	18	40433	14,5	21,25
965301102100160	PG 21	16	150	28	20	40433	16	27
965301102900160	PG 29	16	170	32	28	40433	22	35,5

