





**TECHNIC MASONRY DRILL BIT |
ROUND SHANK | HEAVY DUTY**



20% Faster drilling 20% greater drilling life. Easier drilling = less energy. Depth Markings = greater precision

Rapidez: +20%. Duración de vida: +20%. Mayor confort con menor energía. Graduación= profundidad controlada.

Rapidità : +20%. Durata di vita: +20%. Più confort con meno energia .Graduato = per verificare la profondità.



Concrete
Hormigón
Cemento



Stone
Piedra
Pietra


1096052	EAN	Ø	L	I	QTY PCB	
10960520300	3221912022974	3	60	34	1	3
10960520400	3221912022981	4	75	40	1	3
10960520500	3221912022998	5	85	50	1	3
10960520600	3221912023001	6	100	60	1	3
10960520700	3221912023018	7	100	60	1	3
10960520800	3221912023025	8	120	72	1	3
10960520900	3221912023032	9	120	72	1	3
10960521000	3221912023049	10	120	72	1	3
10960521200	3221912023056	12	150	92	1	1



1096054	EAN	Ø	L	I	QTY PCB	
10960540300	3221912031761	3	60	34	1	3
10960540400	3221912031778	4	75	40	1	3
10960540500	3221912031785	5	85	50	1	3
10960540600	3221912031792	6	100	60	1	3
10960540700	3221912031808	7	100	60	1	3
10960540800	3221912031815	8	120	72	1	3
10960540900	3221912031822	9	120	72	1	3
10960541000	3221912031839	10	120	72	1	3
10960541200	3221912031846	12	150	92	1	1



INDUSTRIAL MASONRY BIT | ROUND SHANK | HEAVY DUTY



Brazed Carbide Tip for accurate holes and increased durability. Depth marking = greater precision.

Resistencia y rapidez. Plaquita de metal duro afilada y soldada a alta temperatura. Graduación= profundidad controlada

Resistenza e velocità. Placchetta in carburo affilata e saldata ad alte temperature. Graduato = per verificare la profondità.



Concrete
Hormigón
Cemento



Stone
Piedra
Pietra

1096032	EAN	Ø	L	I	QTY PCB	
10960320300	3221910840655	3	60	30	1	3
10960320400	3221910840662	4	75	40	1	3
10960320500	3221910840679	5	85	50	1	3
10960320600	3221910840686	6	100	60	1	3
10960320700	3221910840693	7	100	60	1	3
10960320800	3221910840709	8	120	80	1	3
10960320900	3221910840716	9	120	80	1	3
10960321000	3221910840723	10	120	80	1	3




1096032	EAN	Ø	L	I	QTY PCB	
10960321100	3221910840730	11	150	90	1	1
10960321200	3221910840747	12	150	90	1	1
10960321300	3221910840754	13	150	90	1	1
10960321400	3221910840761	14	150	90	1	1
10960321500	3221910840778	15	160	100	1	1
10960321600	3221910840785	16	160	100	1	1
10960321800	3221910840792	18	160	100	1	1
10960322000	3221910840808	20	160	100	1	1



**PROFESSIONAL MASONRY BIT |
ROUND SHANK | HEAVY DUTY**

**BROCA HORMIGÓN IND / MANGO
CILÍNDRICO / USO INTENSIVO**

**PUNTA CEMENTO IND | CODOLO
CILINDRICO | USO INTENSIVO**




Durability & fast drilling . Brazed Carbide Tip

Resistencia y rapidez. Plaquita de carburo afilada y soldada a alta temperatura.

Resistenza e velocità. Placchetta in carburo affilata e saldata ad alte temperatura.



Concrete
Hormigón
Cemento



Stone
Piedra
Pietra





1090031	EAN	Ø	L	I	QTY PCB	
10900310300	3221910081010	3	60	30	1	10
10900310400	3221910081027	4	75	40	1	10
10900310500	3221910081034	5	85	50	1	10
10900310600	3221910081041	6	100	60	1	10
10900310700	3221910081058	7	100	60	1	10
10900310800	3221910081065	8	120	80	1	10
10900310900	3221910081072	9	120	80	1	5
10900311000	3221910081089	10	120	80	1	5



**PROFESSIONAL MASONRY BIT |
ROUND SHANK | GEN PURPOSE**

**BROCA HORMIGÓN PRO / MANGO
CILÍNDRICO / USO CORRIENTE**

**PUNTA CEMENTO PRO | CODOLO
CILINDRICO | USO CORRENTE**



Brazed Carbide Tip for accurate holes and increased durability

Precisión y buena resistencia gracias a su plaquita de metal duro soldada a alta temperatura

Precisione e buona resistenza grazie alla sua placchetta in carburo affilata e saldata ad alte temperatura.



Stone
Piedra
Pietra



Breeze block
Bloque hormigón
Blocco di pietra



Brick
ladrillo
Mattone



1090022	EAN	Ø	L	I	QTY PCB	
10900220300	3221910001827	3	60	30	2	6
10900220400	3221910001834	4	75	40	2	6
10900220500	3221910001841	5	85	50	2	6
10900220600	3221910001858	6	100	60	1	6
10900220700	3221910001872	7	100	60	1	6
10900220800	3221910001889	8	120	80	1	6
10900220900	3221910001896	9	120	80	1	6
10900221000	3221910001902	10	120	80	1	6
10900221100	3221910001919	11	150	90	1	1
10900221200	3221910001926	12	150	90	1	1
10900221300	3221910001933	13	150	90	1	1



1090022	EAN	Ø	L	I	QTY PCB
10900221400	3221910001940	14	150	90	1 1
10900221500	3221910001957	15	150	90	1 1
10900221600	3221910001964	16	150	90	1 1
10900221800	3221910001971	18	160	100	1 1
10900222000	3221910001988	20	160	100	1 1

1090024	EAN	Ø	L	I	QTY PCB
10900240300	3221910027407	3	60	30	2 6
10900240400	3221910027414	4	75	40	2 6
10900240500	3221910027421	5	85	50	2 6
10900240600	3221910027438	6	100	60	1 6
10900240700	3221910027445	7	100	60	1 6
10900240800	3221910027452	8	120	80	1 6
10900240900	3221910027469	9	120	80	1 6
10900241000	3221910027476	10	120	80	1 6
10900241100	3221910027483	11	150	90	1 1
10900241200	3221910027490	12	150	90	1 1
10900241300	3221910027506	13	150	90	1 1
10900241400	3221910027513	14	150	90	1 1
10900241500	3221910027520	15	150	90	1 1
10900241600	3221910027537	16	150	90	1 1
10900241800	3221910027544	18	160	100	1 1
10900242000	3221910027551	20	160	100	1 1

1090026	EAN	Ø	L	I	QTY PCB
10900260300	3221910079994	3	60	30	10 1
10900260400	3221910080006	4	75	40	10 1
10900260500	3221910080013	5	85	50	10 1
10900260600	3221910080020	6	100	60	10 1
10900260700	3221910080037	7	100	60	10 1
10900260800	3221910080044	8	120	80	10 1
10900260900	3221910080051	9	120	80	5 1
10900261000	3221910080068	10	120	80	5 1


1090021	EAN	Ø	L	I	QTY PCB
10900210300	3221910053512	3	60	30	1 10
10900210400	3221910053543	4	75	40	1 10
10900210500	3221910053550	5	85	50	1 10
10900210600	3221910053574	6	100	60	1 10
10900210700	3221910053598	7	100	60	1 10
10900210800	3221910053604	8	120	80	1 10
10900210900	3221910053611	9	120	80	1 5
10900211000	3221910053628	10	120	80	1 5



PROFESSIONAL MASONRY BIT | XL | ROUND SHANK | GEN PURPOSE.

BROCA HORMIGÓN PRO | XL | MANGO CILÍNDRICO | USO CORRIENTE

PUNTA CEMENTO PRO | XL | CODOLO CILINDRICO | USO CORRIENTE



Brazed Carbide Tip for accurate holes and increased durability

Precisión y buena resistencia gracias a su plaqueta de metal duro soldada a alta temperatura

Precisione e buona resistenza grazie alla sua placchetta in carburo affilata e saldata ad alte temperature.



Stone
Piedra
Pietra



Breeze block
Bloque hormigón
Blocco di pietra



Brick
ladrillo
Mattone

1090072	EAN	Ø	L	I	QTY PCB
10900720600	3221910002510	6	200	140	1 1
10900720800	3221910002527	8	200	140	1 1
10900721000	3221910002534	10	200	140	1 1
10900721200	3221910002541	12	200	140	1 1
10900721400	3221910002558	14	200	140	1 1
10900721600	3221910002565	16	200	140	1 1
10900721800	3221910079581	18	200	140	1 1

