

Perfor keményfém marók dolgozó élhossza (mm)

z2	M8507	P645, P646A		P651, P652A	M8500	P602, P615H		M8509	P657, P658A	M8510
z3		P647, P648A		P653, P654A		P603, P616H	P621U		P610, P660A	
z4-6			P649, P650A	P655, P656A		P604, P617H	P623U		P661, P662A	
D 0,5	0,75				1,5			2,5		4
D 1	1,5	3	3		3	3		5		8
D 1,5	2,25	3	4		4	5		7,5		12
D 2	3	3	4	6	5	7		10		16
D 2,5		3	4	7	7	7		12,5		20
D 3		4	5	7	10	9	14	15	25	24
D 3,5		4	6	7	10	12				
D 4		5	8	8	12	14	16		25	32
D 4,5		5	8	8	12	14				
D 5		6	9	10	14	16	16		25	40
D 6		7	10	13	16	19	19		25	48
D 7		8	11	13	18	19				
D 8		9	12	16	20	21	21		25	
D 9		10	13	16	22	22				
D10		11	14	19	26	22	25		38	
D11					28	25				
D12		12	16	22	30	25	25		75	
D14		14	18	22	35	30			75	
D16		16	22	26		32	32		75	
D18		18	24	26		35			75	
D20		20	26	32		38	38		75	
D22						38				
D25						38				

Perfor keményfém marók teljes hossza (mm)

z2	M8507	P645, P646A		P651, P652A	M8500	P602, P615H		M8509	P657, P658A	M8510
z3		P647, P648A		P653, P654A		P603, P616H	P621U		P610, P660A	
z4-6			P649, P650A	P655, P656A		P604, P617H	P623U		P661, P662A	
D 0,5	39				39			39		39
D 1	39	38	38		39	39		39		39
D 1,5	39	38	38		39	39		39		44
D 2	39	38	38	38	39	39		39		44
D 2,5		38	38	38	39	39		45		60
D 3		38	38	38	44	39	39	46	75	60
D 3,5		50	50	57	44	51				
D 4		54	54	57	52	51	51		75	75
D 4,5		54	54	57	52	51				
D 5		54	54	57	52	51	51		75	75
D 6		54	54	57	52	64	64		75	80
D 7		58	58	63	63	64				
D 8		58	58	63	63	64	64		75	
D 9		66	66	72	72	70				
D10		66	66	72	72	70	70		100	
D11					83	70				
D12		73	73	83	83	76	76		150	
D14		75	75	83	83	89			150	
D16		82	82	92		89	89		150	
D18		84	84	92		102			150	
D20		92	92	104		102	102		150	
D22						102				
D25						102				

P...H = HARD-CUT bevonat 50 HRC-ig
P...A = ALCRONA bevonat 54 HRC-ig
P...U = ULTRA-CUT bevonat 65 HRC-ig